



APC Smart-UPS SRT 2200VA 120V

SRT2200XLA

Call for More Information 800-800-4272

- High density, double-conversion on-line power protection with scalable runtime
- Includes: CD with software, Documentation CD, Installation guide, Removable support feet, USB cable, Warranty card


Output	
Output power capacity	1.8kWatts / 2.2kVA
Max Configurable Power (Watts)	1.8kWatts / 2.2kVA
Nominal Output Voltage	120V
Output Voltage Distortion	Less than 2%
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Load Crest Factor	3 : 1
Topology	Double Conversion Online
Waveform type	Sine wave
Output Connections	(6) NEMA 5-20R (Battery Backup) (1) NEMA L5-20R (Battery Backup)
Bypass	Internal Bypass (Automatic and Manual)

Input	
Nominal Input Voltage	120V
Input frequency	40 - 70 Hz (auto sensing)
Input Connections	NEMA 5-20P
Cord Length	6ft (1.83meters)
Number of Power Cords	1

Batteries & Runtime	
Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Included Battery Modules	1

Technical Specifications

APC Smart-UPS SRT 2200VA 120V | SRT2200XLA | Downloaded on 06/24/2020 (EST)

Batteries & Runtime	
Typical recharge time	3hour(s)
Nominal Battery Voltage	72V
Replacement Battery	SRT72RMBPUS 
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Battery Charge Power (Watts)	102Watts
Extendable Run Time	1
Battery Volt-Amp-Hour Capacity	306
Extended Run Options	APC-Smart-UPS-SRT-2200VA-120V (Available in Technical Tab on site)
Runtime	View Runtime Graph (Available in Technical Tab on site) View Runtime Chart (Available in Technical Tab on site)
Efficiency	View Efficiency Graph (Available in Technical Tab on site)

Communications & Management	
Interface Port(s)	RJ-45 Serial, Smart-Slot, USB
Control panel	Multi-function LCD status and control console
Audible Alarm	Audible and visible alarms prioritized by severity
Emergency Power Off (EPO)	Yes
Available SmartSlot™ Interface Quantity	1

Surge Protection and Filtering	
Surge energy rating	340Joules
Filtering	--

Physical	
Maximum Height	17.0inches (432MM, 43.2CM)
Maximum Width	3.35inches (85MM, 8.5CM)
Maximum Depth	23.0inches (584MM, 58.4CM)
Net Weight	55.0lbs. (25.0KG)
Shipping weight	68.0lbs. (30.84KG)
Shipping Height	9.7inches (246MM, 24.6CM)

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Physical	
Shipping Width	23.6inches (599MM, 59.9CM)
Shipping Depth	31.9inches (810MM, 81.0CM)
Color	Black
Units per Pallet	12.0

Environmental	
Operating Temperature	32 - 104 °F (0 - 40 °C)
Operating Relative Humidity	0 - 95 (non-condensing) %
Operating Elevation	0-10000ft (0-3000meters)
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 (non-condensing) %
Storage Elevation	0-50000ft (0-15000meters)
Online thermal dissipation	535.0BTU/hr
Protection Class	IP 20

Conformance	
Approvals	CSA C22.2 No.107.3-05, ENERGY STAR V2.0 (USA), FCC Part 15 Class A, UL 1778
Standard warranty	3 years repair or replace (excluding battery) and 2 years for battery

Sustainable Offer Status	
RoHS	Compliant
REACH	REACH: Contains SVHCs
Proposition 65 Warning	Available in Documentation tab